

# BETA RANGE

## Beta Maxi Quick Release

---



HEAT PRESS TECHNOLOGY



# Beta Maxi Quick Release

**A high quality technologically advanced** low cost manual press, ideal for most users. The swing head operation gives a perfect view of the transfer and garment allowing accurate and easy application, along with safety of operation. Fitted with our unique advanced computerised controller to accurately monitor both temperature and time. Pressure adjustment is by a fingertip control knob making this machine ideal for both light and heavy pressure requirements.

**The Beta Maxi** has the option of five printbed areas, to give you the perfect transfer.

**The Beta Maxi is a manually operated** heat presses for transfer printing and material fusing. They are ideal for medium volume production.

**The work areas** of the Beta Maxi is: 15 x 20 ins (38 x 50 cms) but machines may have, to special order, optional smaller sized interchangeable worktables of any size and various shapes within these table sizes.

Sizes	Specifications	European Machine	Specifications	USA Machine
15.3cm x 15.3cm	Power Consumption	2500 Watts	Power Consumption	1600 Watts
20.5cm x 20.5cm	Power Supply	230-240 Volts AC	Power Supply	120 Volts AC
25.4cm x 25.4cm	Working temperature	70-230°C	Working temperature	160-455°F
30.5cm x 30.5cm	Display Timer Range	0 - 9.59 mins	Display Timer Range	0 - 9.59 mins
38cm x 38cm	Machine height open	65 cms	Machine height open	25.5 ins
	Machine height closed	35 cms	Machine height closed	14 ins
	Machine width	51 cms	Machine width	20 ins
	Machine width, loading	94 cms	Machine width, loading	37 ins
	Machine depth	89 cms	Machine depth	35 ins
	Machine depth, loading	120 cms	Machine depth, loading	41 ins
	Work area required	110 x 92 x 64 cms	Work area required	43 x 36 x 25 ins
	Weight export packed	52 kg	Weight export packed	114.5 lbs
	Size export packed	91(L) x 62(W) x 42 cms(H)	Size export packed	36(L) x 24.5(W) x 16.5 ins(H)
	Net weight	45 kg	Net weight	99 lbs
	Press pad dimensions	38 x 50 cms	Press pad dimensions	15 x 20 ins
	Fuses	12.5 A	Fuses	16 A
	A-weighted noise level	<70 dB(A)	A-weighted noise level	<70 dB(A)